

BARRIER GATE

Half Height Swing Gates



Model: NW-SW-04

Size: L1400mm*W180mm* H965mm

FEATURES

- Anti-Pinch mechanical structure, anti-bumps function, when the swing arm reset process meet resistance, within a limited time automatically stops the motor, the default delay after the reset again (until reset), and the force is very small ($\leq 2\text{Kg}$)
- Anti-intrusion function, when the gate signal is not received, the arm will be locked automatically.
- With automatic reset function, after the gate opening, within a specified period no entry, the system will automatically cancel the user's access Permissions
- Adjustable normally open or normally closed, to meet the requirements of different venues
- Compatible with a most reader device, integrate via dry contact signal
- Unidirectional or bidirectional control of personnel access
- Remote control and management by the management computer
- Fail-Safe mode to meet fire safety requirements

Application

- The station, wharf, tourist attractions management of import & export channels.
- Convention and exhibition, swimming pool and recount channel management
- Enterprises import and export of attendance, entrance guard, consumption management
- Special exclusive control

Remark

- Highspeed barrier gate function: all the function is similar, difference lies in the outlook.
- Custom development: all products (software/hardware) can be customized according to user's actual demand or set

Technical Parameters

- Material 304 Stainless Steel/ Powder-Coated
- IP Rating: 54
- Pass Rate: 30-35 person/min
- Lane Width: 600 - 900 mm
- Power: 230VAC 50Hz
- MTBF: 5,000,000 cycles



SMART BUILDING SOLUTION