NW-FH-01(120)

Full Height Turnstiles

Product of Singapore



FEATURES

- Access gate mechanism consist of two parts: Stainless Steel main frame and cylindrical center core. Access Control Reader can be install on the main frame.
- Access direction: singular or bi-direction (optional). Prevent anti-directional access, Access granted and allow to pass through one direction at a time, the other side will remain lock; the timing can be configured.
- Self-resetting function will allow the turnstiles to lock when there's no passenger passes through. This timing can be pre-set or adjustable.
- Fail-Safe or Fail-Secure mode can be programmed to comply building requirement. (optional)
- LED directional indicator function to display authorize passage on both direction.
- Equipped with Micro-Controller board with counting function using LED digital display. (optional).
- Equipped with Micro-Controller board with memory function for group access. (optional)
- Seamless entry upon receiving control signal

TECHNICAL SPECIFICATION

Power voltage	AC220±10%, 50Hz
Drive voltage	DC24V
Operation condition	-15°C ~ +60°C
Relative humidity	None-condensation
Input signal	O VDC, Dry contact
Working current	≤2000mA
Length of bar	480mm
Service life	≥5 million

Dimensions (L x W x H)	1600 x 1500 x 2300mm
Open angle	90° / 120°(optional)
Pass speed	≤30person/minute
Cabinet Material	304/316 Stainless steel Hairline finishing (optional)
Open direction	Single or Bi-Directional (optional)
Working environment	Indoor or Outdoor
IP Degree	IP43
Width of Passage	≤670mm