NW-SA-02

Half Height Single Arm

Product of Singapore



FEATURES

- Problem self-recovery & corrective measure ability, convenient maintain & adjust.
- Motherboard with high clean sound read chips which could broadcast inlight of user's requirement.
- Human base model indication function, real time displaying improve the passing rate and convenient maintain
- Automatic counting indicating passenger's number (optional)
- Resetting automatically auto cancel the pass through and closed barrier in case nothing pass the channel in a setting time
- Anti pinch function with UPS to meet fire-safety requirement
- Break-in, tail over-pass and reverse alert function to maintain high security
- Standard input / output port, meanwhile leaving a port space for installing RS485 communication, connect and manage the intergrated systems through the remote PC
- Super Combination capacity, adjustable model on site, adjustable speed of barrier slide Open signal with memory or withoutset function

TECHNICAL SPECIFICATION

Power voltage	AC220±10%, 50Hz
Drive Voltage	AC12V + AC18V
Operation condition	-15°C ~ +60°C
Relative humidity	None-condensation
Input signal	0 VDC, Dry contact
Working current	≤2000mA
Service life	≥5 million times
Panel Type	Stainless steel

Dimension (L x W x H)	1200 x 220 x 980mm
Open angle	90°
Pass speed	≤30 person/minute
Cabinet Material	304/316 Stainless steel Hairline finishing (optional)
Open Direction	Single and Bi-directional (optional)
Work environment	Indoor or Semi-outdoor
IP Degree	IP54
Passage Width	600-900mm