NW-SW-01

Half Height Swing Gate

Product of Singapore



FEATURES

- Fault self-test and alarm functions, convenient user maintenance and using
- Via the Built-in Controller Board, Programmable devices running status
- Anti-Pinch mechanical structure, anti-bumps function, when the swing arm reset process meet resistance, within a limited time automatically stops the motor, the default delay after the reset again (until reset), and the force is very small (≤2kg)
- Anti-intrusion function, when the gate signal is not received, the arm will locked automatically.
- With automatic reset function, after the gate opening, within a specified period of time not pass, the system will automatically cancel the user's access Permissions
- Adjustable normally open or normally closed, in order to meet the requirements of different venues
- Compatiable with a most reader device, integrate via dry contact signal
- Unidirectional or bidirectional control of personnel access
- Remote control and management by the management computer
- Fail-Safe mode to meet fire safety requirements

TECHNICAL SPECIFICATION

Power voltage	AC220±10%, 50Hz
Drive Voltage	DC24V
Operation condition	-15°C ~ +60°C
Relative humidity	≤95%, None-condensation
Input signal	0 VDC, Dry contact
Working current	≤2000mA
Service life	≥5 million times
Panel Type	Acrylic / Tempered Glass (optional)

Dimension (L x W x H)	1400 x 200 x 1020mm
Length of flap	290-440mm
Pass speed	≤30 person/minute
Cabinet Material	304/316 Stainless steel Hairline finishing (optional)
Open Direction	Single and Bi-directional (optional)
Work environment	Indoor or Outdoor
IP Degree	IP54
Passage Width	600-900mm